LTS LOVE TO SHINE
















Colours	Article no.	EAN
silver	665954	4043544752666
black	665955	4043544752673
white	665956	4043544752680







Description

- surface-mounted luminaire in rectangular design for ceiling/wall and diverse lighting tasks
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- housing and partly integrated mounting box made from sheet steel
- tool-free snap-in and slide mechanism between housing and mounting box
- protruding lens optics made from matt PMMA
- direct screwing on of the mounting box
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

Notes

For vertical mounting the weight force must point in the locking direction.

Standard options



Special options









Lighting data / Norms

Lamps LED Modul / CRI 80 / 3000 K

L90 B50 50.000 h **Lifetime**L80 B50 100.000 h
L80 B20 50.000 h

System power $44.1 \, \mathrm{W}$ Luminaire luminous flux $6470 \, \mathrm{lm}$ System efficiency $146.71 \, \mathrm{lm/W}$ Module efficiency $160.00 \, \mathrm{lm/W}$ UGR class≤25Beam rangeWide Flood

Beam angle 60°

Supply voltage 220 - 240 V / 50 - 60 Hz

Protection class | Type of protection | IP20

Dimensions / Weights

 Length
 587 mm

 Width
 130 mm

 Height
 50 mm

 Net weight
 2.38 kg


 Gross weight
 2.49 kg

Ceiling and Pendant Luminaires rectangular · LUZ Surface-Mounted


LTS LOVE TO SHINE

LUZ-A22 106.830.60/DALI

LUZ | Surface-Mounted (1xLED 44W 830/3000K 6470lm 60°)



	C0	C90	C180	C270
0°	784	784	784	784
15°	876	863	876	863
30°	350	393	350	393
45°	116	124	116	124
60°	56	54	56	54
75°	32	28	32	28
90°	7	2	7	2



η	LED	
Efficiency	147 lm/W	
Direct/Indirect	↓ 99% / ↑ 1%	
System Power	44 W	
UGR	X=4H, Y=8H	
Reflection factors	70/50/20	
UGR C0/C180	22.8	
UGR C90/C270	22.5	
CIE Flux Codes	76 90 97 99 100	
Ra/CRI	>80	

LTS

Accessories



ZB-OR DONGLEOrganic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOROrganic Response sensor for surface mounting