



Workstation Luminaires

LUZ06-A 14.007.30



Colours	Article no.	EAN
black	655296	4043544640642
silver	655297	4043544640659
white	655298	4043544640666



Description

- linear luminaire for surface mounting
- symmetrical and wide-beam light distribution (beam angle 60°)
- outstanding ease of maintenance
- no UV and thermal emissions
- housing and partly integrated mounting box made from sheet steel
- tool-free snap-in and slide mechanism between housing and mounting box
- lens optics made from transparent high-gloss PMMA
- easy screw fixing of the mounting box
- 5-pole terminal block
- ballast (LED converter) integrated

Notes

For vertical mounting the weight force must point in the locking direction.

Standard options



Special options



Lighting data / Norms

Lamps	LED Matrix / CRI 85 / 3000 K
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	24.0 W
Luminaire luminous flux	3170 lm
System efficiency	132.08 lm/W
Module efficiency	152.00 lm/W
UGR class	≤19
Beam range	Wide Flood
Beam angle	60°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


Dimensions / Weights

Length	1153 mm
Width	67 mm
Height	58 mm
Net weight	3.20 kg
Gross weight	3.37 kg

LUZ06-A 14.007.30

LUZ06-A 14.007.30

LUZ | Surface-Mounted (1xLED 24W 830/3000K 3170lm)



	C0	C90	C180	C270
0°	749	749	749	749
15°	763	759	763	759
30°	546	535	546	535
45°	114	108	114	108
60°	30	20	30	20
75°	15	9	15	9
90°	4	1	4	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	4.11	4.08	263.7
6.0	8.22	8.15	65.9
9.0	12.33	12.23	29.3
12.0	16.44	16.31	16.5
15.0	20.56	20.39	10.5

η	LED
Efficiency	132 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	24 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	16.9
UGR C90/C270	16.3
CIE Flux Codes	85 96 99 100 100
Ra/CRI	>80

LTS