


LUNXS 201.830.1/DALI



Colours	Article no.	EAN
silver	665668	4043544749819
black	665669	4043544749826
white	665670	4043544749833



Description

- can be used as ceiling, wall or pendant luminaire (suspension to be ordered separately)
- direct illumination with light-effect ring
- outstanding ease of maintenance
- no UV and thermal emissions
- luminaire consisting of sheet steel housing for ballast and light unit
- light unit can be separated from ballast housing without tools via bayonet catch (with safety rope)
- opal acrylic glass diffuser
- ballast housing for direct screw mounting
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

Standard options



Special options



Lighting data / Norms


Lamps	LED linear / CRI 80 / 3000 K
EPREL light sources	993702
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	18.3 W
Luminaire luminous flux	1700 lm
System efficiency	92.89 lm/W
Module efficiency	163.00 lm/W
UGR class	≤22
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20

Dimensions / Weights

Outer diameter	400 mm
Height	94 mm
Net weight	4.12 kg
Gross weight	4.34 kg

LUNXS 201.830.1/DALI

Lunata XSmall (1xLED 18W 830/3000K 1700lm)



	C0	C90	C180	C270
0°	344	344	344	344
15°	330	330	330	330
30°	292	292	292	292
45°	232	232	232	232
60°	155	155	155	155
75°	66	66	66	66
90°	2	2	2	2
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	C0-C180 Plane: 9.20	C90-C270 Plane: 9.22	64.9
6.0	18.40	18.44	16.2
9.0	27.60	27.66	7.2
12.0	36.80	36.88	4.1
15.0	46.00	46.10	2.6

η	LED
Efficiency	94 lm/W
Direct/Indirect	↓ 99% / ↑ 1%
System Power	18 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	21.7
UGR C90/C270	21.7
CIE Flux Codes	47 79 96 99 100
Ra/CRI	>80

LTS

Accessories



L 83/1500 DIM
wire-rope kit 3-fold
(length: 1500 mm, 5-core cable)



L 83/3000 DIM
wire-rope kit 3-fold
(length: 3000 mm, 5-core cable)



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
Organic Response sensor for surface mounting



ZB-OR-P SENSOR/3000
Organic Response sensor for pendant mounting