


Pendant

PLL 52.1200.840.1/DALI



Description

- prestigious ceiling and pendant luminaire with square design for homogeneous and sophisticated architectural lighting
- no UV and thermal emissions
- aluminium housing with removable LED unit
- wire-rope suspension to be ordered separately
- opal insert pane made from acrylic glass
- easy ceiling screw mounting of the housing
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

Standard options




Special options



Colours	Article no.	EAN
silver	633959	4043544359551
white	633960	4043544359568
black	642294	4043544480811



Lighting data / Norms

Lamps	LED Matrix / CRI 80 / 4000 K
EPREL light sources	832757
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	179.1 W
Luminaire luminous flux	26430 lm
System efficiency	147.57 lm/W
Module efficiency	200.00 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20



Dimensions / Weights

Length	1200 mm
Width	1200 mm
Height	105 mm
Net weight	30.40 kg
Gross weight	85.00 kg




Pendant

PLL 52.1200.840.1/DALI

PLL 52.1200.840.1/DALI

PL 52 (1xLED 179W 840/4000K 26430lm)

— C0/C180 cd / 1000 lm — C90/C270



	C0	C90	C180	C270
0°	365	365	365	365
15°	346	348	346	348
30°	300	301	300	301
45°	233	233	233	233
60°	152	153	152	153
75°	63	64	63	64
90°	1	1	1	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	8.36	8.43	1072.7
6.0	16.72	16.85	268.2
9.0	25.09	25.28	119.2
12.0	33.45	33.70	67.0
15.0	41.81	42.13	42.9

η	LED
Efficiency	148 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	179 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	22.5
UGR C90/C270	22.5
CIE Flux Codes	48 80 96 100 100
Ra/CRI	>80

LTS

Accessories



L 72/3000 DIM
wire-rope kit 4-fold
(length: 3000 mm, 5-core cable)



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-A SENSOR
Organic Response sensor for surface mounting



ZB-OR-P SENSOR/3000
Organic Response sensor for pendant mounting