

# LUNM 204.840.1/DALI



Colours	Article no.	EAN
silver	665761	4043544750747
black	665762	4043544750754
white	665763	4043544750761

## Description

- can be used as ceiling, wall or pendant luminaire (suspension to be ordered separately)
- direct illumination with light-effect ring
- outstanding ease of maintenance
- no UV and thermal emissions
- luminaire consisting of sheet steel housing for ballast and light unit
- light unit can be separated from ballast housing without tools via bayonet catch (with safety rope)
- opal acrylic glass diffuser
- ballast housing for direct screw mounting
- 5-pole terminal block
- ballast (LED converter) integrated (with DALI dimming)

## Standard options



## Special options




## Lighting data / Norms

Lamps	LED linear / CRI 80 / 4000 K
EPREL light sources	993703 993701
	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
Lifetime	
System power	37.7 W
Luminaire luminous flux	4900 lm
System efficiency	129.97 lm/W
Module efficiency	175.00 lm/W
UGR class	≤22
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I
Type of protection	IP20


## Dimensions / Weights

Outer diameter	856 mm
Height	95 mm
Net weight	14.90 kg
Gross weight	19.00 kg



# LUNM 204.840.1/DALI

Lunata Medium (1xLED 38W 840/4000K 4900lm)



	C0	C90	C180	C270
0°	345	345	345	345
15°	332	332	332	332
30°	294	294	294	294
45°	234	233	234	233
60°	155	157	155	157
75°	66	66	66	66
90°	1	1	1	1
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	9.23	9.20	187.8
6.0	18.47	18.41	47.0
9.0	27.70	27.61	20.9
12.0	36.94	36.82	11.7
15.0	46.17	46.02	7.5

<b>η</b>	LED
Efficiency	129 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	38 W
<b>UGR</b>	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.0
UGR C90/C270	20.0
CIE Flux Codes	47 79 96 100 100
Ra/CRI	>80

LTS

## Accessories



**L 72/3000 DIM**  
wire-rope kit 4-fold  
(length: 3000 mm, 5-core cable)



**ZB-OR DONGLE**  
Organic Response IR dongle kit



**ZB-OR GATEWAY**  
Organic Response IoT Gateway Cascade Series



**ZB-OR-A SENSOR**  
Organic Response sensor for surface mounting



**ZB-OR-P SENSOR/3000**  
Organic Response sensor for pendant mounting