

# LK-LED 060.1130.R12.090/DALI




## Description

- light-insert with integrated LED light strips for Lichtkanal 060 Curved profile LKDI-P 060.R12.090 OAG
- consisting of one linear light-insert (length = 705 mm) and radial collimators for directing linear light through a curve (radius: 1230 mm, angle: 90°)
- no UV and thermal emissions
- reflectors of the linear light-inserts made from white-painted aluminium
- radial collimators made from polycarbonate
- through-wiring kit included
- light-control foil curved "opal diffuse" included, linear light-inserts with curved PMMA diffusers for uniform light distribution
- tool-free snapping into Lichtkanal profile
- 5-pole terminal block, pre-fabricated for through-wiring
- ballast (LED converter DALI, dimmable) integrated

## Notes

The linear thermal expansion of the aluminium profile is about 0.3 mm per meter at  $dT = 10$  Kelvin.

Colours	Article no.	EAN
	660014	4043544792082



## Standard options



## Special options



## Lighting data / Norms

Lamps	LED linear / CRI 80 / 3000 K
EPREL light sources	833889
Lifetime	L90 B50 50.000 h
	L80 B50 100.000 h
	L80 B20 50.000 h
System power	78.3 W
Luminaire luminous flux	9060 lm
System efficiency	127.71 lm/W
Module efficiency	181.52 lm/W
UGR class	≤25
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	I

## Dimensions / Weights

Length	2684 mm
Width	50 mm
Height	38 mm
Net weight	1.30 kg
Gross weight	1.40 kg

