

SCEKLP 33.2040.25



| Colours | Article no. | EAN |
|---------|-------------|---------------|
| black | 619033 | 4043544406200 |
| white | 619040 | 4043544406224 |
| silver | 619048 | 4043544406217 |
| | | |









Description

- flexible recessed spotlight system consisting of recessed frames, light-heads and ballasts (recessed frames to be ordered separately)
- light-head pivots through 30° on gimbals
- outstanding ease of maintenance
- no UV and thermal emissions
- thermal management with passive cooling (heat sink made from aluminium)
- gimbals made from die-cast zinc
- specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting
- · clear safety glass
- tool-free installation into mounting frame via flexible retaining springs
- connection to ballast via luminaire cable with Mini-Clamp connector
- ballast (LED converter) included (external placement)

Standard options



Special options



Lighting data / Norms

Lamps EPREL light sources

Lifetime

System power Luminaire luminous flux System efficiency Module efficiency UGR class Beam range Beam angle Supply voltage Protection class Type of protection

848119 L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h 25.8 W 2890 lm 112.01 lm/W 160.37 lm/W ≤19 Medium Flood 23 220 - 240 V / 50 - 60 Hz Ш IP20

LED Spot/CRI 80/4000 K

Dimensions / Weights


| Height | 140 mm |
|------------------------|---------|
| Recessed depth | 138 mm |
| Diameter of light head | 155 mm |
| Net weight | 1.10 kg |
| Gross weight | 1.16 kg |

Recessed Spotlights · Scene 33 System


SCEKLP 33.2040.25

SCEKLP 33.2040.25

Scene 33 System | Light-Head (1xLED 26W 840/4000K 2890Im 25°)



| | C0 | C90 | C180 | C270 | |
|--------------|------|------|------|------|--|
| 0° | 3436 | 3436 | 3436 | 3436 | |
| 15° | 954 | 954 | 954 | 954 | |
| 30° | 388 | 388 | 388 | 388 | |
| 45° | 28 | 28 | 28 | 28 | |
| 60° | 6 | 6 | 6 | 6 | |
| 75° | 2 | 2 | 2 | 2 | |
| 90° | 0 | 0 | 0 | 0 | |
| cd / 1000 lm | | | | | |
| | | | | | |



| η | LED 1111 lm/W ↓ 100% / ↑ 0% 26 W | | |
|--------------------|---|--|--|
| Efficiency | | | |
| Direct/Indirect | | | |
| System Power | | | |
| UGR | X=4H, Y=8H | | |
| Reflection factors | 70/50/20 | | |
| UGR C0/C180 | 18.4 | | |
| UGR C90/C270 | 18.4 | | |
| CIE Flux Codes | 96 99 100 100 100 | | |
| Ra/CRI | > 80 | | |

Accessories



SCER 33.100 mounting frame 1-lamp



SCER 33.200 mounting frame 2-lamp



SCER 33.300 mounting frame 3-lamp



SCER 33.400 mounting frame 4-lamp

