

VTRL 13.0530.25/DALI



Description


- recessed spotlight with round recessed funnel
- reflector lens pivots through 20°
- outstanding ease of maintenance
- no UV and thermal emissions
- innovative thermal management with passive cooling
- recessed funnel and heat sink made from die-cast aluminium
- high-tech reflector lens made from PMMA for high luminous efficiency and glare-free lighting
- tool-free ceiling mounting via quick-action clamping springs (automatic adjustment of the ceiling thickness)
- luminaire and ballast permanently connected via cable (length: 500 mm), ballast ready for mains connection
- ballast (LED converter DALI, dimmable) included (external placement)

Standard options



Colours	Article no.	EAN
white	641878	4043544462077

Special options





Lighting data / Norms

Lamps	LED Spot / CRI 80 / 3000 K
EPREL light sources	871340
Lifetime	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
System power	12.0 W
Luminaire luminous flux	1100 lm
System efficiency	91.66 lm/W
Module efficiency	128.30 lm/W
UGR class	≤19
Beam range	Medium Flood
Beam angle	26°
Supply voltage	220 - 240 V / 50 - 60 Hz
Protection class	II
Type of protection	IP40

Dimensions / Weights


Outer diameter	110 mm
Height	108 mm
Cut-out (Ø)	95 mm
Ceiling thickness	10.0 - 15.0 mm
Recessed depth	122 mm
Diameter of light head	50 mm
Net weight	0.59 kg
Gross weight	0.64 kg



VTRL 13.0530.25/DALI

Vale-Tu Round Large (1xLED 12W 830/3000K 1100lm)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	3667	3667	3667	3667
15°	1509	1509	1509	1509
30°	227	227	227	227
45°	27	27	27	27
60°	6	6	6	6
75°	0	0	0	0
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	1.42	448.2
6.0	2.83	112.0
9.0	4.25	49.8
12.0	5.66	28.0
15.0	7.08	17.9

η	LED
Efficiency	92 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	12 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	17.7
UGR C90/C270	17.7
CIE Flux Codes	97 100 100 100 100
Ra/CRI	>80

LTS

Accessories



ZB-OR DONGLE
Organic Response IR dongle kit



ZB-OR GATEWAY
Organic Response IoT Gateway Cascade Series



ZB-OR-R SENSOR
Organic Response sensor for recessed mounting