




Encastrement

# ML-R 070.10830.2 AOB/DALI

## ML-R 070.10830.2 AOB/DALI

Monoline 070 | Recessed (1xLED 17W 830/3000K 2520lm)



	C0	C90	C180	C270
0°	404	404	404	404
15°	380	380	380	380
30°	314	316	314	316
45°	230	228	230	228
60°	144	140	144	140
75°	61	57	61	57
90°	1	1	1	1

cd / 1000 lm

Offset [m]	Cone width [m]		Illuminance [lx]
3.0	7.11	7.01	113.2
6.0	14.22	14.02	28.3
9.0	21.33	21.02	12.6
12.0	28.43	28.03	7.1
15.0	35.54	35.04	4.5

<b>η</b>	LED
Efficiency	148 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	17 W
<b>UGR</b>	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	24.5
UGR C90/C270	24.2
CIE Flux Codes	51 81 96 100 100
Ra/CRI	>80

LTS

### Accessoires



**ZB-OR DONGLE**  
Organic Response kit dongle IR



**ZB-OR GATEWAY**  
Organic Response passerelle IoT série Cascade



**ZB-OR-R SENSOR**  
capteur Organic Response pour montage encastré