


SCEKLP 33.5030.25

SCEKLP 33.5030.25

Scene 33 System | Light-Head (1xLED 52W 830/3000K 5580lm 25°)

C0/C180 cd / 1000 lm



	C0	C90	C180	C270
0°	3473	3473	3473	3473
15°	966	966	966	966
30°	374	374	374	374
45°	21	21	21	21
60°	5	5	5	5
75°	1	1	1	1
90°	0	0	0	0
cd / 1000 lm				

Offset [m] Cone width [m] Illuminance [lx]

Offset [m]	Cone width [m]	Illuminance [lx]
3.0	1.22	2153.0
6.0	2.43	538.3
9.0	3.65	239.2
12.0	4.86	134.6
15.0	6.08	86.1


η	LED
Efficiency	108 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	52 W
UGR	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	20.5
UGR C90/C270	20.5
CIE Flux Codes	97 100 100 100 100
Ra/CRI	>80

LTS

Accessoires




SCER 33.100
Boîtier à encastrement à 1 point de lumière



SCER 33.200
Boîtier à encastrement à 2 points de lumière



SCER 33.300
Boîtier à encastrement à 3 points de lumière



SCER 33.400
Boîtier à encastrement à 4 points de lumière