


# PLL 23.0675.840.1/DALI



## Beschreibung

- repräsentative Wandleuchte in rundem Design für homogene Beleuchtung und anspruchsvolle architektonische Lichtgestaltung
- keine UV- und Wärmestrahlung
- Stahlblechgehäuse über Bajonettverschluss abnehmbar
- Acrylglascheibe opal
- Montageplatte für einfache Schraubbefestigung
- 5-polige Anschlussklemme
- Betriebsgerät (LED-Konverter) integriert (mit DALI Dimmung)

## Standardoptionen



## Sonderoptionen





## Lichttechnik / Normen

<b>Leuchtmittel</b>	LED linear / CRI 80 / 4000 K
<b>Lebensdauer</b>	L90 B50 50.000 h L80 B50 100.000 h L80 B20 50.000 h
<b>Systemleistung</b>	66.7 W
<b>Leuchten-Lichtstrom</b>	7350 lm
<b>Systemeffizienz</b>	110.19 lm/W
<b>Moduleffizienz</b>	154.00 lm/W
<b>UGR Klasse</b>	≤25
<b>Versorgungsspannung</b>	220 - 240 V / 50 - 60 Hz
<b>Schutzklasse</b>	I
<b>Schutzart</b>	IP20

## Abmessungen / Gewichte

<b>Außendurchmesser</b>	675 mm
<b>Höhe</b>	123 mm
<b>Nettogewicht</b>	9.62 kg
<b>Bruttogewicht</b>	11.06 kg

Farbe	Artikelnummer	EAN
silber	633919	4043544359155
weiß	633920	4043544359162
schwarz	642277	4043544480644




# PLL 23.0675.840.1/DALI

## PLL 23.0675.840.1/DALI

PL 23 (1xLED 67W 840/4000K 7350lm)

— C0/C180 cd / 1000 lm — C90/C270



	C0	C90	C180	C270
0°	355	355	355	355
15°	340	339	340	339
30°	298	297	298	297
45°	234	234	234	234
60°	154	155	154	155
75°	65	65	65	65
90°	0	0	0	0
cd / 1000 lm				

Offset [m]	Cone width [m]		Illuminance [lx]
	C0-C180 Plane	C90-C270 Plane	
3.0	8.88	8.86	289.9
6.0	17.76	17.72	72.5
9.0	26.64	26.59	32.2
12.0	35.53	35.45	18.1
15.0	44.41	44.31	11.6

<b>η</b>	LED
Efficiency	110 lm/W
Direct/Indirect	↓ 100% / ↑ 0%
System Power	67 W
<b>UGR</b>	X=4H, Y=8H
Reflection factors	70/50/20
UGR C0/C180	23.0
UGR C90/C270	23.0
CIE Flux Codes	47 79 96 100 100
Ra/CRI	>80

LTS

## Zubehör



**ZB-OR DONGLE**  
Organic Response IR-Dongle-Set



**ZB-OR GATEWAY**  
Organic Response IoT-Gateway Kaskadenserie



**ZB-OR-A SENSOR**  
Organic Response Sensor für Anbaumontage



**ZB-OR-P SENSOR/3000**  
Organic Response Sensor für Pendelmontage